



## 1055 – Tandem Booster

Design:	T-1 fabricated frame, low profile design with 9 air bags controlled with high volume regulator and accumulator air tanks for equal pressure. Frame has 4-pin connection for Peerless/Scona style booster adapters. D-rings included for lifting unladen booster.
Structural Capacity:	45,000 lbs.
Dimensions:	Width: 8'6" Overall Length: 20' including adapter
Adapter:	Clamp on style adapter to fit Peerless/Scona live roll trailers.
Landing Legs:	Dual pin drop leg; for unladen use only.
Suspension:	Peerless rubber bushed walking beam suspension. 60" axle spacing.
Axles (2):	Self-steering, 25k axles with air dampers on tie rods, 16-1/2" x 7" Q plus brakes rated to 22,500 pounds with type 30/30 spring brakes, oil seals, and Haldex auto slacks.
Hubs and Drums (4):	10 stud steel Unimount hubs, cast brake drums
Wheels (8):	10 Hole Unimount wheels
Tires (8):	275/70R22.5
Electrical System:	FMVSS/CMVSS approved with Trucklite LED lights and harnesses. Four prong long load plug installed.
Strobe Lights:	Trucklite LED strobe lights mounted in rear bumper complete with weatherproof switch.
Air System:	FMVSS/CMVSS approved. Remote air drains provided for air tanks. Cover installed over air tanks.
Sign Pockets:	Pockets on back of light box for wide load sign.
Mud Flaps:	Black Scona.
Paint:	Cleaned, sandblasted, primed and painted one color paint.